



## OAK DOOR GUIDELINES

In order to validate any Warranty or manufacturers guarantee, the following advisory notes in relation to the storage, finishing, and maintenance of the products must be followed.

1. In relation to the storage of products the Customer must:

- a) Store the products in a cool, dry atmosphere
- b) Store the products in a flat position
- c) Ensure that the products are not exposed to a damp room; and
- d) Ensure the products are not exposed to any form of direct heat.

2. In relation to the finishing of the products that are intended for external use the customer must:

- a) Seal the relevant products immediately after unpacking and prior to the hanging procedure, by generously applying one base coat of "Sikkens HLS plus" and a minimum of two top coats of "Sikkens Filter 7 plus" or alternatively one base coat of "Sadolin Ultra base coat" and a minimum of two top coats of "Sadolin Ultra Highly Translucent Wood Stain" to the front, back, sides, top and bottom; and
- b) Additionally seal any planed edges and cut outs during the hanging procedure, so no moisture ingress can occur

3. In relation to the finishing of the products that are unfinished and intended for internal use the customer must:

- a) Seal the door immediately after unpacking and prior to the hanging procedure, by applying at least three coats of an oil based varnish or paint to the front, back, sides, top and bottom;
- b) Additionally seal any planed edges and cut outs during the hanging procedure; and
- c) Seal the timber using Rubio Monocoat Oil UV R2 (UV catalysed finishing oil).

4. In relation to the maintenance of the products, it is suggested that every three (3) years each product is lightly sanded and a refresher coat applied